

Sport 67

PRODUCT SPECIFICATION

Key Features

- > Hard-wearing vinyl sports floor
- > Wood designs & solid colours available
- > Sheet format in 6.7mm gauge
- > Conforms to EN14904
- > For use in 'multi-purpose' indoor sports arenas



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	6.7mm
Total Weight		3600g/m ²

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 18.5m	4	-	37m ²

Performance Requirements	Standard	Result
General Performance	EN 14904 ASTM F2772	Meets Conforms
Sliding Coefficient of Friction	EN 13036	80 - 110
Shock Absorption	EN 14808	Pass
Ball Rebound	EN 12235	Pass
Vertical Deformation	EN 14809	Pass
Reaction to Fire	EN 13501-1 CAN/ULC S102.2	Class Cfl-S1 FSV < 300; SDV < 500
Abrasion Resistance	EN 649 ISO 5470-1	Group T <1000mg
Impact Resistance	EN 1517	Pass
Resistance to Indentation	EN 1516	Pass
Specular Gloss	ISO 2813	≤30%
Rolling-Load Resistance	EN 1569	Pass

Sustainability	Standard	Result
Recyclable		100%
Recycled Content		24%
FloorScore		Certified

Maintenance Performance**Standard****Result****Resistance to Chemicals**

ISO 26987 (EN 423)

Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Polyflor Sport 67 is reinforced with polyurethane for improved cleaning and maintenance. Polyflor Sport 67 should not have a polish applied.



BS EN 14041



EN 14041

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1

Sport 67




RANGE SHADES



Green 7515 w/r 7515
NCS S 5030-G10Y LRV 18



Blue 7512 w/r 7512
NCS S 5030-R90B LRV 15



Oak 7518 w/r 7518
NCS S 4030-Y40R LRV 22



Maple 7516 w/r 7516
NCS S 3030-Y20R LRV 37

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.