

# Polysafe Wood fx Acoustix PUR



## PRODUCT SPECIFICATION

### Key Features

- > High clarity wood effect safety vinyl flooring
- > Impact Sound Reduction of 19dB
- > Pendulum test - 36+ (slider 96)
- > Sustainable slip resistant safety flooring
- > Polysafe PUR for superior cleaning benefits



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.7mm
Wear Layer	ISO 24340 (EN 429)	0.65mm
Total Weight	ISO 23997 (EN 430)	2670g/m <sup>2</sup>
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	8	-	40m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 11638 (EN 651)	Conforms
Use Area	ISO 10874 (EN 685)	23, 34, 42
Enhanced Slip Resistance	EN 13845 AS 4586 RRL Pendulum Test Surface Roughness	Esf R10 ≥36 (wet test - 4S Rubber / Slider 96) Rz ≥20µm
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2	Class Bfl-S1 Class 1 FSV < 300; SDV < 500
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1	≤0.20mm

Sustainability	Standard	Result
BRE Green Guide		A+ ENP 415
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product

<b>FloorScore</b>		Certified
<b>AgBB/ABG</b>		Pass
<b>Responsible Sourcing</b>	BES 6001	Excellent

## Acoustic Performance

	Standard	Result
<b>Impact Sound Reduction</b>	ISO 10140-3	19dB

## Maintenance Performance

	Standard	Result
<b>Resistance to Chemicals</b>	ISO 26987 (EN 423)	Good resistance
<b>Alco Hand Gels</b>	Compatible for use with most commonly used alco-based hand gels	
<b>Steam Cleaning</b>	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



### Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

# Polysafe Wood fx Acoustix PUR

## RANGE SHADES


### PARQUET DESIGNS



**Eton Oak Parquet 3399**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9822 LRV 24



**Parish Oak Parquet 3398**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9841 LRV 32



**American Oak 3382**  
plank size in sheet: 100 x 1000mm  
w/r 3380 LRV 37



**Sun Bleached Oak 3384**  
plank size in sheet: 200 x 1500mm  
w/r 3372 LRV 31



**Rustic Oak 3332**  
plank size in sheet: 83 x 333/666mm  
w/r 3330 LRV 26



**Silver Oak 3352**  
plank size in sheet: 83 x 333/666mm  
w/r 3237 LRV 23



**European Oak 3342**  
plank size in sheet: 100 x 1000mm  
w/r 3340 LRV 23



**Aged Oak 3389**  
plank size in sheet: 200 x 1500mm  
w/r 9824 LRV 9

w/r - Weld Rod

LRV - Light Reflectance Value

### Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1